

# Telco skirting heater – GIU / GIUS

Type	El-number	Power	Height	Length	Depth	Description
GIU 03	54 490 05	300 W	79 mm	575 mm	83 mm	Normal-temperature skirting heater with switchbox for permanent installation.
GIU 07	54 490 06	700 W	79 mm	1116 mm	83 mm	
GIU 10	54 490 07	1000 W	79 mm	1616 mm	83 mm	
GIU 13	54 490 08	1300 W	79 mm	2116 mm	83 mm	
GIUS 03	54 490 15	300 W	79 mm	575 mm	83 mm	Normal-temperature skirting heater with cable and plug
GIUS 07	54 490 16	700 W	79 mm	1116 mm	83 mm	
GIUS 10	54 490 17	1000 W	79 mm	1616 mm	83 mm	
GIUS 13	54 490 18	1300 W	79 mm	2116 mm	83 mm	
Floor brackets:	54 490 20					

Telco's skirting heaters type GIU/ GIUS are tried and tested flow-through heaters with high -quality mechanical thermostats. These heaters have a splashproof design and are suitable for use in all types of rooms, both wet and dry.

GIU and GIUS is particularly well suited to eliminating draughts below large window panes that reach all the way, or nearly all the way, down to the floor.

The heaters are manufactured from extruded aluminum sections. The complete heating element is also made from aluminum and incorporates a heating coil, insulation, cooling fins and connection lead in one unit. This is a tried and tested design that provides excellent heat distribution and a long lifetime.

The heaters can be lacquered in special colours and supplied with curtain protection and floor brackets.



Specifications
Flow-through heater with on/off switch, bi-metal thermostat and thermal cut-out
230 V
Colour: Pearl white
Splash proof and rustproof; can be used in wet rooms.
Connection: Right-hand side.
Fittings to wall: Heaters must be fitted horizontally and are delivered with solid wall brackets.
Floor installation: Heaters can be fitted to the floor using floor brackets that need to be ordered separately
Max. surface temperature: 82°C
Night set-back: Heater types GIU are equipped for control via a control wire (fixed lowering of 3,5°C)

Installation distance requirements	GIU / GIUS
Minimum distance to side wall:	2 cm
Minimum distance to floor:	5 cm
Minimum distance to ceiling or window sill:	20 cm