

# Telco skirting heater – MEU / MEUS

Type	El-number	Power	Height	Length	Depth	Description
MEU 03	54 491 01	300 W	82 mm	530 mm	84 mm	Normal-temperature skirting heater with switchbox for permanent installation.
MEU 07	54 491 02	700 W	82 mm	1075 mm	84 mm	
MEU 10	54 491 03	1000 W	82 mm	1570 mm	84 mm	
MEU 13	54 491 04	1300 W	82 mm	2070 mm	84 mm	
MEUS 03	54 491 11	300 W	82 mm	530 mm	84 mm	Normal-temperature skirting heater with cable and plug
MEUS 07	54 491 12	700 W	82 mm	1075 mm	84 mm	
MEUS 10	54 491 13	1000 W	82 mm	1570 mm	84 mm	
MEUS 13	54 491 14	1300 W	82 mm	2070 mm	84 mm	
Floor brackets	54 490 20					

Skirting heaters type MEU and MEUS are flow-through heaters with a very accurate electronic thermostat that enables the heater to maintain a constant temperature. They are suitable for use in all types of rooms, both wet and dry. The heaters are NEMKO approved with protection classification IP 24.

MEU and MEUS is particularly well suited to eliminating draughts below large window panes that reach all the way, or nearly all the way, down to the floor.

The heaters are manufactured from extruded aluminum sections. The complete heating element is also made from aluminum and incorporates a heating coil, insulation, cooling fins and connection lead in one unit. This is a tried and tested design that provides excellent heat distribution and a long lifetime. To prevent contact between metal parts, we use heat-resistant silicon mats as inserts when fastening elements.

The heaters can be lacquered in special colours and supplied with curtain protection and floor brackets.



Specifications
Flow-through heater with on/off-switch. Electronic thermostat and thermal cut-out.
230 V
Colour: RAL 9016 white
Splash proof (IP 24) and rustproof; can be used in wet rooms.
Connection: Right-hand side.
Fittings to wall: Heaters must be fitted horizontally and are delivered with solid wall brackets.
Floor installation: Heaters can be fitted to the floor using floor brackets that need to be ordered separately
Max. surface temperature: 82°C
Night set-back: Heater types MEU are equipped for control via a control wire (fixed lowering of 3,5°C)

Installation distance requirements	MEU / MEUS
Minimum distance to side wall:	2 cm
Minimum distance to floor:	5 cm
Minimum distance to ceiling or window sill:	20 cm