

Telco interior heater – TIU / TIUS / TU

Type	El-number	Power	Height	Length	Depth	Description
TIU 03	54 490 25	300 W	150 mm	403 mm	86 mm	Normal-temperature heater with switchbox for permanent installation.
TIU 08	54 490 26	800 W	150 mm	682 mm	86 mm	
TIU 12	54 490 27	1200 W	150 mm	893 mm	86 mm	
TIU 16	54 490 28	1600 W	150 mm	1157 mm	86 mm	
TIUS 03	54 490 30	300 W	150 mm	403 mm	86 mm	Normal-temperature heater with cable and plug
TIUS 08	54 490 31	800 W	150 mm	682 mm	86 mm	
TIUS 12	54 490 32	1200 W	150 mm	893 mm	86 mm	
TIUS 16	54 490 33	1600 W	150 mm	1157 mm	86 mm	
TU 03	54 490 35	300 W	150 mm	353 mm	86 mm	Normal-temperature heater for permanent installation, and external control
TU 08	54 490 36	800 W	150 mm	632 mm	86 mm	
TU 12	54 490 37	1200 W	150 mm	843 mm	86 mm	
TU 16	54 490 38	1600 W	150 mm	1107 mm	86 mm	
Floor brackets:	54 490 45					

Telco's interior heaters type TIU / TIUS are tried and tested flow-through heaters with high -quality mechanical thermostats. Type TU is for external control and permanent installation. All these heaters have a splashproof design and are suitable for use in all types of rooms, both wet and dry.

They have higher power per length unit than most other heaters on the market, and is therefore well suited to bathrooms and other rooms with high heating requirements and limited space.

The heaters are manufactured from extruded aluminum sections. The complete heating element is also made from aluminum and incorporates a heating coil, insulation, cooling fins and connection lead in one unit. This is a tried and tested design that provides excellent heat distribution and a long lifetime.

The heaters can be lacquered in special colours and supplied with curtain protection and floor brackets.



Specifications
Flow-through heater with thermal cut-out
230 V
Colour: Pearl white
Splash proof and rustproof; can be used in wet rooms.
Connection: Right-hand side.
Fittings to wall: Heaters must be fitted horizontally and are delivered with solid wall brackets.
Floor installation: Heaters can be fitted to the floor using floor brackets that need to be ordered separately
Max. surface temperature: 44°C
Night set-back: Heater types TIU are equipped for control via a control wire (fixed lowering of 3,5°C)

Installation distance requirements	TIU / TIUS / TU
Minimum distance to side wall:	2 cm
Minimum distance to floor:	5 cm
Minimum distance to ceiling or window sill:	30 cm